


## ESSPx-Ku50 SSPA/SSPB Ku-Band 50W GaN



ESSPx-Ku50 R12K15

### DESCRIPTION

The ESSPx is the outdoor solid-state power amplifiers (SSPAs) series designed and manufactured by Elber with GaN transistor technology, with output power from 50W up to 200W. Available also as SSPB with in-house designed upconverter, the ESSPA-Ku50 is the 50W Ku-band version. The ESSPx is an integrated unit, comprehensive of power supply and cooling system, housed in a weather-proof cabinet for safe outdoor installation and operation. Safe operation is preserved also through automatic software/hardware shutdown of final stages in case of over-temperature, over-current and high reflected power. The amplifier is equipped with precise forward and reflected power detection circuitry for correct configuration and monitoring of the amplifier. Combination of basic pallets is just mechanical through waveguide combiners, so that performances can be easily replicated for massive production. Management of the unit can be done either locally (with Hand-held controller) and remotely through serial RS-485/422 or Ethernet connection. A redundancy kit is also available, with autonomous management of 1:1 solution or optionally with external Master control unit, through Cleber platform (one control unit for 2 amplifiers).

### FEATURES

- SSPA and SSPB
- GaN Technology
- Output power 50 W ( $P_{SAT}$ )
- High Gain and Linearity
- Fully Outdoor Use
- Fully protected against over-temperature, over-current and high VSWR.
- Gain adjustment
- Output sample monitor port
- Autonomous 1+1 redundancy management
- Remote Monitor & Control through Serial and Ethernet ports

## SPECIFICATIONS

### General:

|                           |   |
|---------------------------|---|
| Frequency:                | 14.0-14.5 GHz (standard)<br>13.75-14.5 GHz (extended) |
| Output Power:             | +47.0 dBm $P_{SAT}$<br>+43.0 dBm $P_{LIN}$            |
| Gain (@ 0dB attenuation): | 78 dB $\pm$ 2 dB                                      |
| Gain adjustment:          | 15 dB in 0.1 dB steps                                 |
| Gain flatness:            | $\pm$ 0.75 dB over any 40MHz band                     |
| Gain flatness:            | $\pm$ 1.5 dB over full band                           |
| Spectral Regrowth:        | <-30 dBc (@1.0 x SR QPSK/8PSK)                        |
| Spurious Emissions:       | <-55 dBc @ $P_{LIN}$                                  |
| AM/PM Conversion:         | 2.0°/dB (max) @ $P_{LIN}$                             |
| Group Delay Ripple:       | < 1 ns <sub>p-p</sub>                                 |
| Input:                    |   |
| Connector:                | N (f)   |
| Impedance:                | 50 ohms   |
| VSWR :                    | 1.3:1   |
| Output:                   |   |
| Flange:                   | WR75  |
| Impedance:                | 50 ohms   |
| VSWR:                     | 1.23:1 with isolator                                  |
| Output Sample:            |   |
| Connector:                | N (f)   |
| Impedance:                | 50 ohms   |
| VSWR:                     | 1.3:1   |

### BUC (Optional):

|   |   |
|---|---|
| L-Band frequency:                                 | 950-1450 MHz (standard)<br>950-1700 MHz (extended)  |
| Local Oscillator:                                 | 13.050 GHz (standard)<br>12.800 GHz (extended)  |
| AGC Range:  | 0 to -25 dBm  |
| Input:  |   |
| Connector:  | N (f)   |
| Impedance:  | 50 ohms   |
| VSWR:   | 1.4:1   |
| Reference:  | Internal and/or External  |
| • Internal (Multiplexed on N(f) connector IF IN): |   |
| Frequency:  | 10 MHz  |
| Aging/day:  | $\pm 2 \times 10^{-10}$   |
| Aging/year:                                       | $\pm 5 \times 10^{-8}$  |
| Stability:  | $\pm 2 \times 10^{-8}$  |
| Phase Noise:                                      | - 53 dBc/Hz @ 10 Hz<br>- 70 dBc/Hz @ 100 Hz<br>- 90 dBc/Hz @ 1 kHz<br>- 100 dBc/Hz @ 10 kHz<br>- 103 dBc/Hz @ 100 kHz |
| • External:                                       |   |
| Frequency:  | 10 MHz  |
| Level:  | -15 to +5 dBm   |
| Connector:  | BNC (f), 50 ohms  |

### Phase Noise (min):

- 120 dBc/Hz @ 10 Hz
- 135 dBc/Hz @ 100 Hz
- 150 dBc/Hz @ 1 kHz
- 155 dBc/Hz @ 10 kHz
- 160 dBc/Hz @ 100 kHz

### Control:

- Stand-alone:  
RS-485  
RS-232  
Ethernet (custom cable required)
- With M&C unit CLEBER:  
Ethernet 10/100BaseT  
Connector: Amphenol - PT07Y12-14P

### Redundancy (Optional):

|                       |  |
|-----------------------|--|
| Configuration:        | 1:1  |
| Control:              | Autonomous via dedicated line.<br>Remotely controlled by M&C unit CLEBER |
| Waveguide switch:     |  |
| Frequency Range:      | 10.0 - 15.0 GHz  |
| Flange:               | WR75   |
| VSWR (MAX):           | 1.08 : 1 (1.05:1 TYP)  |
| Insertion Loss (Max): | 0.05 dB  |
| Isolation (Min.):     | 60 dB  |
| Switching Time:       | 50ms typical   |
| Load:                 |  |
| Typical Load:         | 400 W  |
| Flange:               | WR75   |

### Electrical:

|              |   |
|--------------|---|
| Supply:      | 90-265 V~ 47-63 Hz<br>40 to 60 V <sub>dc</sub> (optional) |
| Connector:   | HIRSCHMANN 932322100                                      |
| Consumption: | 230W @ $P_{LIN}$  |

### Mechanical:

|             |        |
|-------------|--------|
| Dimensions: |        |
| Width       | 250 mm |
| Height      | 240 mm |
| Depth       | 520 mm |
| Weight:     | 6 Kg   |

### Environmental:

|                              |                 |
|------------------------------|-----------------|
| Operative temperature range: | -10 ÷ 55°C      |
| Humidity:                    | 100% condensing |

CE Marking

\* Elber reserves the right to make changes to specifications of products described in this datasheet at any time without notice and without obligation to notify any person of such changes.



ELBER Srl. Via Pontevecchio, 42W - 16042 Carasco (GE) Italy  
Phone +39.0185.351333 fax +39.0185.351300  
www.elber.com - elber@elber.it