

ESSPX-KU200-2

SSPA/SSPB Ku-Band 200W GaN



The ESSPx-Ku-2 is the outdoor solid-state power amplifiers (SSPAs) series designed and manufactured by Elber with GaN transistor technology, with output power from 100W up to 400W. Available also as SSPB, with in-house designed upconverter, the ESSPA-Ku200-2 is the 200W Ku-band version.

The ESSPx is an integrated unit, comprehensive of power supply and cooling system, housed in a weatherproof cabinet for safe outdoor installation and operation. Safe operation is preserved also through automatic software/hardware shutdown of final stages in case of overtemperature, over-current and high reflected power.

The amplifier is equipped with precise forward and reflected power detection circuitry for correct configuration and monitoring of the amplifier. Combination of basic pallets is just mechanical through waveguide combiners, so that performances can be easily replicated for massive production. Management of the unit can be done either locally and remotely through serial Ethernet connection.

A redundancy kit is also available, with autonomous management of 1:1 solution or optionally with external Master control unit, through Cleber platform (one control unit for 2 amplifiers).

MAIN FEATURES

- SSPA and SSPB
- GaN Technology
- Output power 200 W (P_{SAT})
- High Gain and Linearity
- Fully Outdoor Use
- Fully protected against over-temperature, overcurrent and high VSWR
- Gain adjustment
- Output sample monitor port
- Autonomous 1+1 redundancy management
- Remote Monitor & Control through Serial and Ethernet ports

SPECIFICATIONS

GENERAL

Frequency:	14.0-14.5 GHz (standard) 13.75-14.5 GHz (extended)
Output Power:	+53.0 dBm (200W) P_{SAT} +50.0 dBm (100W) P_{LIN}
Gain @ 0 dB attenuation:	78 dB \pm 2 dB
Gain regulation:	20dB in 0.1 dB steps
Spectral regrowth:	<-30 dBc @1.0 x SR
Third order IMD:	-25 dBc (2 tones 5 MHz separation @ P_{LIN})
Gain flatness:	\pm 0.75 dB over any 40 MHz band \pm 1.5dB full band
Gain variation over temp:	\pm 0.3 dB
Power Meter accuracy:	\pm 1 dB max
NPD in Tx Band:	-80 dBm/Hz
NPD in Rx Band:	-150 dBm/Hz
Spurious level @ P_{LIN}:	<-60 dBc
AM/PM conversion:	2.0°/dB max at P_{LIN}
Group Delay Ripple:	<1ns p-p (in any 36MHz band)
Input:	
Connector:	N (f)
Impedance:	50 ohms
VSWR:	1.3:1
Output:	
Flange:	WR75
Impedance:	50 ohms
VSWR:	1.23:1 with output isolator
Output Sample:	
Connector:	N (f)
Impedance:	50 ohms
VSWR:	1.3:1

BUC

L-Band frequency:	950-1450 MHz (standard) 950-1700 MHz (extended)
Local Oscillator:	13.050 GHz (standard) 12.800 GHz (extended)
Input:	
Connector:	N (f)
Impedance:	50 ohms
VSWR:	1.4:1
Cable AGC range:	0 ÷ -25 dBm
Reference frequency:	10 MHz (internal or external)
Reference input:	Multiplexed on N-type IF IN
Reference level:	-15 ÷ +5 dBm
Oscillator:	
Frequency:	10 MHz
Aging/day:	\pm 2 x 10 ⁻¹⁰
Aging/year:	\pm 5 x 10 ⁻⁸
Stability:	\pm 2 x 10 ⁻⁸
Phase Noise:	- 53 dBc/Hz @ 10 Hz - 70 dBc/Hz @ 100 Hz - 90 dBc/Hz @ 1 kHz - 98 dBc/Hz @ 10 kHz - 100 dBc/Hz @ 100 kHz - 120 dBc/Hz @ 1 MHz

CONTROL

Stand-alone:	Ethernet (Http/SNMP) RS232 RS485
With M&C unit CLEBER:	Http; SNMP Connector: Amphenol - PT07Y12-14P

REDUNDANCY (OPTIONAL)

Configuration:	1:1
Control:	Autonomous via dedicated line Remotely controlled by M&C unit CLEBER
Waveguide switch:	
Frequency Range:	10.0 - 15.0 GHz
Flange:	WR75
VSWR (MAX):	1.08 : 1 (1.05:1 TYP)
Insertion Loss (Max):	0.05 dB
Isolation (Min.):	60 dB
Switching Time:	50ms typical
Load:	
Typical Load:	400 W
Flange:	WR75

ELECTRICAL

Supply:	90-265 V~ 47-63 Hz
Connector:	HIRSCHMANN 932322100
Consumption:	750 W @ P_{LIN} 1050 W @ P_{SAT}
Field Replaceable	
Relay Field Replaceable	

MECHANICAL

Dimensions:	
Width:	230 mm
Height:	225 mm
Depth:	390 mm
Weight:	25 Kg

ENVIRONMENTAL

Operative temperature range:	-30÷ 55°C
Humidity:	100% condensing
CE Marking	

Elber reserves the right to make changes to specifications of products described in this datasheet at any time without notice and without obligation to notify any person of such changes.